EUROPEAN PATENT OFFICE

Patent Abstracts of Japan





PUBLICATION NUMBER : 56027330 PUBLICATION DATE : 17-03-81

APPLICATION DATE 15-08-79
APPLICATION NUMBER 54104410

APPLICANT: YOSHINO KOGYOSHO CO LTD;

INVENTOR: AKUTSU MASAO;


INT.CL. : B29D 23/03 // C08J 7/08


TITLE : HEAT TREATMENT FOR INTERNAL

WALL SURFACE OF SATURATED

POLYESTER RESIN BIAXIALLY

STRETCHED BOTTLE





ABSTRACT :

PURPOSE: To simply undergo the heat treatment of an internal portion of a resin bottle by a method wherein after the resin bottle is molded by the use of a stretching rod, compressed air for molding is exhausted by the stretching rod, at the same time combustion gas is sent in and an ignition plug provided in the stretching rod is fired for explosion and combustion.

CONSTITUTION: After a cold parrison 1 which was ingection-molded previously is inserted into a metal mold 2 and an stretching rod 4 is placed in the parrison 1, compressed air is blown in from the stretching rod 4 and the parrison is stretched biaxially to obtain the bottle 8. Next, the compressed air is exhausted from the compressed air exhaust passage 6 of the stretching rod 4 without removing the bottle 8 and the stretching rod 4, then combustion gas is taken through a gas blow-in passage 5 and an ignition plug 7 is bired for explosion and combustion.

COPYRIGHT: (C)1981, JPO& Japio

